

## ST 3.60 C5

PORTABLE POWER

WATERPUMP Range AQUALINE INTENS

#### **PRODUCT ADVANTAGES**

- HONDA Professional Engine
- Automatic priming
- Offeres accessories

STAGE V (2016/1628 EU) : This product is compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe

#### Range AQUALINE INTENS

Designed for water with low solid content.



# ST 3.60 C5

### WATER PUMP SPECIFICATIONS

Range	AQUALINE INTENS		
Type liquid	Clear water with little sediment pump		
Suction diameter [mm]	76		
Backflow diameter (mm)	76		
Outflow maximum (L/min)	900		
Outlflow maximum (m3/h)	54		
Lifting height (m)	26		
Suction height (m)	8		
Granulometry (mm)	8		
Automatic priming	Yes		
Fuel	Petrol		
Tank (L)	3,10		
75% cons. (l/h) *	0,90		
75% Autonomy (h) *	3,40		
Sound power level guaranteed LwA dB(A)	105		
Acoustic pressure level @1m in dB(A)	90		
Acoustic pressure level @7m in dB(A)	75		

#### **ENGINE SPECIFICATIONS**

Engine brand	HONDA
Engine ref.	GX160_C5
Engine Type	O.H.V.
Start	Starter
Oil shutdown	Oui
Displacement (cm3)	163
Oil system capacity including filters (I)	0,60

### DIMENSIONS AND WEIGHT

Length (cm)	50,50
Width (cm)	41,40
Height (cm)	44,80
Dry Weight (kg)	29

#### PACKAGING

Packaging type	Box
Length (cm)	52
Width (cm)	42,50
Height (cm)	46,50
Weight (kg)	32
Pallet type	120/80
Number of box by pallet	12
Pallet height (cm)	153
weight of the packaged Pallet (kg)	394



ST 3.60 C5 - PORTABLE POWER - WATERPUMP AQUALINE INTENS This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. \*ISO 8528.

SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 - France - Tél. +33 (0)2 98 41 41 41 - www.kohlersdmo.com



## ST 3.60 C5

	Inlet filter		80	Circlips
	Screw-on connect	ors		User and maintenance manual
OPTIONS				
I I I I I I I I I I I I I I I I I I I	RBH1	Box of 24 o.5L	cans of oil or 20 1 L cans of oi	I (SAE 15W40)
in the second seco	RBH0-5	Box of 24 0.5L	cans of oil or 20 1 L cans of oi	I (SAE 15W40).
arms arm	RHO	Cover for SDM	IO 's generating sets, welding s	sets and water pumps
	R12	Piping kit for 3	water pumps made up of 5 m s	suction + 25 m lift.
RÓP	R14	Rapid connect	ions kit for 3 water pumps.	



ST 3.60 C5 - PORTABLE POWER - WATERPUMP AQUALINE INTENS This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. \*ISO 8528. SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 – France - Tél. +33 (0)2 98 41 41 41 - www.kohlersdmo.com