

KOHLER®

SDMO®



DIESEL 15 LC TA SILENCE AVR C5

PORTABLE POWER

GENERATING SET Range DIESEL SILENCE

PRODUCT ADVANTAGES

- Generating set guaranteed 3 years
- KOHLER water-cooled industrial engine
- Very Silent
- Soundproofing and against shocks panels
- Hydrocarbons bulk tank

GENERATOR SMART CARE is a Bluetooth box which can be used on all the brand's portable generators. TECHNOLOGY EQUIPPED WITH AN INNOVATIVE APPLICATION Generator Smart Care is a digital solution which provides access to:- The list of generators- The maintenance due dates- A maintenance aid- The map of reseller partners The APM202 control panel displays overspeed, starting failure, oil pressure, battery and temperature STAGE V (2016/1628 EU) : This product is compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe

Range DIESEL SILENCE

Both long run times and very long life for professional applications.



DIESEL 15 LC TA SILENCE AVR C5

GENERAL SPECIFICATIONS

| | |
|--|----------------|
| Range | DIESEL SILENCE |
| Frequency (Hz) | 50 Hz |
| Max power (kW) * | 9,50 |
| Max power (kVA) | 11,90 |
| Nominal voltage (V) | 400 |
| Number of Phase | Three phase |
| Fuel | Diesel Fuel |
| Tank (L) | 27 |
| 75% cons. (l/h) * | 2,60 |
| 75% Autonomy (h) * | 10,40 |
| Sound power level guaranteed LwA dB(A) | 94 |
| Acoustic pressure level @1m in dB(A) | 78 |
| Acoustic pressure level @7m in dB(A) | 65 |

ENGINE SPECIFICATIONS

| | |
|---|---------------|
| Engine brand | KOHLER |
| Engine ref. | KDW702 |
| Engine Type | Diesel O.H.V. |
| Start | Electrical |
| Oil shutdown | OUI |
| Displacement (cm3) | 686 |
| Oil system capacity including filters (l) | 1,60 |

ALTERNATOR SPECIFICATIONS

| | |
|--------------------------|------------------|
| Technology | Collar and brush |
| AVR Regulation | Yes |
| Indication of protection | IP 23 |
| Insulation class | H |

PLUGS AND PANEL DESCRIPTIVE

1 230V 10/16A socket - circuit breaker + 3 230V 16A sockets - circuit breaker + 1 400V 16A socket - circuit breaker + emergency stop button + hour meter + indicator + APM202

DIMENSIONS AND WEIGHT

| | |
|-----------------|--------|
| Length (cm) | 121,10 |
| Width (cm) | 79 |
| Height (cm) | 105,60 |
| Dry Weight (kg) | 315 |

PACKAGING

| | |
|------------------------------------|--------|
| Packaging type | Box |
| Length (cm) | 122,20 |
| Width (cm) | 80,40 |
| Height (cm) | 105,60 |
| Weight (kg) | 321 |
| Pallet type | |
| Number of box by pallet | 0 |
| Pallet height (cm) | 0 |
| weight of the packaged Pallet (kg) | 0 |

KOHLER®
SDMO®

27/05/2022

DIESEL 15 LC TA SILENCE AVR C5 - PORTABLE POWER - GENERATING SET DIESEL SILENCE

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528.

SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 - France - Tél. +33 (0)2 98 41 41 41 - www.kohlersdmo.com



27/05/2022

DIESEL 15 LC TA SILENCE AVR C5 - PORTABLE POWER - GENERATING SET DIESEL SILENCE

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528.

SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 – France - Tél. +33 (0)2 98 41 41 41 - www.kohlersdmo.com

DIESEL 15 LC TA SILENCE AVR C5

ACCESSORIES SUPPLIED



User and maintenance manual

Battery without maintenance



Lifting eye

Hour meter

OPTIONS



R03B This set includes a differential switch, a hour meter, the plugs and a thermal circuit breaker.



RSTART2 Remote control in order to start or stop the generating set until a distance of 50 meters (needs the APM202 control panel)



VERS050 Switches over automatically if the mains fails, 40A or 100A 1P or if the mains fails, 25A or 40A 3P (needs the installation of a APM202 control panel). Includes the battery charger.



RKDS6 Maintenance kit for KOHLER KDW702



RAP The adaptor for industrial sockets is used to connect 230-V appliances to the industrial socket.



RPM Male plugs for all models made up of : 2 x 16 A/230 V, EEC17: 1 x 16A/230 V, 1 x 32A/230 V and 1 x 16A/400V